

**3M****PROTECTA**

Fall Protection

3M™ Protecta® First™ Fall Protection

Fall protection that's there when you need it.

Every at height worker deserves to be safe, no matter the size or nature of the job. That's why Protecta® products have become the choice of safety managers looking for reliable fall protection solutions that comply with safety regulations and help their workers get the job done.

Learn more about personal safety at
[3M.com.au/FallProtection](https://www.3m.com.au/FallProtection) | 1-3M 1-3M (136 136)

© 3M 2018. All rights reserved. 3M is a trademark of 3M Company.



Fall Protection

3M™ Protecta® First™ Fall Protection

The First™ line of fall protection products from Protecta® were designed around a simple concept; provide a fundamental fall protection line with exceptional value. Utilising extensive research, the First™ line was assembled to provide fall protection in a wide variety of circumstances while maintaining a focus on value and safety. First™ offers all the necessary elements for a complete fall protection system and allows the user to choose components based on personal preference and job constraints. In addition to offering compliance, First™ is built with our quality and reliability, fall protection gear you can trust.

Selection. As simple as ABC.

A typical Personal Fall Arrest System (PFAS) incorporates three components often described as the ABC's of fall protection; The anchorage, body support and connectors.

A Anchorage

are a secure point of attachment. Anchorage connectors vary by industry, job, type of installation and structure. They must be able to hold fast under more than a ton of force generated in a fall.



Tie-off adaptor

- 2m length
 - Provides a fast & safe tie-off for your personal fall protection system
 - Max Arresting Force 6kN
 - Minimum Breaking Strength – 15kN
- AT010621657**

B

Body Support

harnesses distribute fall forces over the upper thighs, pelvis, chest and shoulders. They provide an attachment point on the worker for the personal fall arrest system.



Construction Harness

- Construction harness with front, rear, side D-rings, retrieval attachment points, waist belt and padded hip/lower back pad.
- AT010621582**



Industrial Harness

- Industrial harness with front and rear fall arrest rated D-ring, adjustable leg, chest & pelvic straps.
- AT010621574**



Industrial harness with integral lanyard w/snap hook

- Adjustable 2m Lanyard
 - Snap hook end
- AT010621590**



Industrial harness with integral lanyard w/scaffold hook

- Adjustable 2m Lanyard
 - Scaffold hook end
- AT010621608**

C

Connectors

such as shock absorbing lanyards or self retracting lifelines connect a worker's harness to the anchorage.



EZ-Stop™ Shock Absorbing Lanyard

- 2m Adjustable length
 - Snap Hook ends
 - Alloy Steel – 22.2kN Body, 16kN Gate, 20mm Gate Opening
- AT010621624**



Twin Tail EZ-Stop™ Shock Absorbing Lanyard

- 2m length
 - Twin Tail with Scaffold Hooks
 - Alloy Steel – 22.2kN Body, 16kN Gate, 65mm Gate Opening
- AT010621616**



Rope line

- 1m Web Lanyard with Snap hooks
 - 15m length Ropeline
- AT010621632**

Visit www.3M.com.au/FallProtection to learn more or call 1800 445 867 (Aus) or 0800 212 505 (NZ)

AV011467527

