

**KWIKSEAL 3207/3209FS SOFT PVC CLOSED
CELL FOAM**

- DESCRIPTION:** Low density closed cell PVC foam coated on one side with cured acrylic adhesive. Colour – 3207 Grey & 3209 Black
- PERFORMANCE FEATURES:** Foam is a soft density foam that offers a reliable and comfortable watertight seal at less than 30% compression. Rolls are reverse wound for easy, quick and clean application. Foam is U.V. resistant offering a consistent long lasting seal. Good resistance to dilute acids and alkalis. The foam is also swirl free which allows the user to drill through the foam after it is applied on the job.
- TECHNICAL SPECIFICATIONS:**
- | | | |
|------------------------|---|-----------------------------|
| Adhesive Power | - | 1120 gm/cm |
| Density | - | 120 Kgs/m ³ |
| Tensile Strength | - | >2.69Kgs/cm |
| Elongation | - | 50% |
| Temperature Resistance | - | -40°C to +82°C |
| Hardness (Shore 00): | - | 20-40 Average |
| Thermal Conductivity: | - | 0.30 (btu-in)/hr.sq.ft)(°F) |
| Water Tightness | - | 100%@<30%Compression |
| Water Absorption | - | 12% Max. |
- STANDARD THICKNESSES:** 3207 Grey – 3.2mm; 4.8mm; 6.4mm, 9.5mm, 12.7mm
3209 Black – 3.2mm, 4.8mm, 6.4mm 9.5mm, 12.7mm, 19mm
- WIDTHS AVAILABLE:** 6mm to 1370mm
- APPLICATIONS:** In partitioning, helps reduce sound transmission and compensates for uneven surfaces. In roofing and cladding Industries ideal for sealing between window frames and angled cladding
- APPROVALS:** FMVSS 302 Self extinguishing

The above information is given in good faith for guidance only and not specification purposes. All data is based upon average values, the Purchaser shall be responsible for determining the suitability of this product for their purposes.

May 2003.