

**KWIKSEAL 3257/3259FS MEDIUM PVC CLOSED
CELL FOAM**

DESCRIPTION:

Medium density closed cell PVC foam coated on one side with cured acrylic adhesive. Colour -3257 Grey, 3259 Black.

**PERFORMANCE
FEATURES:**

Foam is a medium density foam that offers a reliable and comfortable watertight seal at less than 30% compression. Rolls are reverse wound for easy, quick and clean application. Foam has good recovery after compression and because of resistant to U.V., dilute acids and alkali's product provides a consistent long lasting seal. The foam is also swirl free which allows the user to drill through the foam after it is applied on the job.

**TECHNICAL
SPECIFICATIONS:**

| | | |
|-------------------------------|---|-------------------------------------|
| Adhesive Power | - | 1120 gm/cm |
| Density | - | 155Kgs/m³ |
| Tensile Strength | - | >6.2Kgs/cm² |
| Elongation | - | 40% |
| Temperature Resistance | - | -40°C to +82°C |
| Hardness (Shore 00): | - | 25-45 |
| Thermal Conductivity: | - | 0.27(btu-in)/(hr.sq.ft.)(°F) |
| Water tightness | - | 100%@<30% Compression |
| Water Absorption | - | 10% Maximum |

**STANDARD
THICKNESSES:**

Grey 3257/1.6mm; 3.2mm; 4.8mm; 6.4mm; 9.5mm; 12.7mm
Black 3259/1.6mm; 3.2mm; 4.8mm; 6.4mm; 9.5mm; 12.7mm.

WIDTHS AVAILABLE:

6mm to 1,370mm.

APPLICATIONS:

Suitable for sealing around electrical panels in petrol pumps; sealing between logs in log kit homes. Ideal for sealing around flanges of rigid duct work. Excellent as a water proof seal in domestic window manufacturing.

APPROVALS:

FMVSS302 Self Extinguishing
RoHS compliant in respect to 2002/95/EC.

The above information is given in good faith for guidance only and not specification purposes. All data is based upon average values, the Purchaser shall be responsible for determining the suitability of this product for their purposes.

September 2007.